

# Indoor units

## Casual

KID-05.3 S  
Standard



Model	KAY-CF 20 DR11	KAY-CF 26 DR11.1	KAY-CF 35 DR11	KAY-CF 52 DR11	KAY-CF 71 DR11
Cooling capacity rated; kW	2.05	2.63	3.52	5.28	7.03
Heating capacity rated; kW	2.64	2.93	3.81	5.57	7.33
Air flow low / medium / high; m <sup>3</sup> /h	259 / 333 / 439	259 / 333 / 439	325 / 430 / 540	540 / 680 / 840	662 / 817 / 980
Sound pressure low / medium / high; dB(A)	25.0 / 31.0 / 38.0	25.0 / 31.0 / 38.0	25 / 34.5 / 40.5	26 / 36 / 42.5	36 / 40.5 / 45
Sound power level; dB(A)	50	50	55	56	59
Width / Height / Depth; mm	715 / 285 / 194	715 / 285 / 194	805 / 285 / 194	957 / 302 / 213	1040 / 327 / 220
Net weight; kg	7.0	7.0	7.6	10	12.3
Communication wiring; mm <sup>2</sup>	(3+T)x2,5	(3+T)x2,5	(3+T)x2,5	(3+T)x2,5	(3+T)x2,5
Liquid / Gas pipe diameter; inch	1/4" / 3/8"	1/4" / 3/8"	1/4" / 3/8"	1/4" / 1/2"	3/8" / 5/8"

See compatibility of controllers in the range 1x1



## Prodigy Pro

KID-06 S  
Standard



Model	KAY-P 26 DR10	KAY-P 35 DR10	KAY-P 52 DR10	KAY-P 71 DR10
Cooling capacity rated; kW	2.72	3.52	5.28	7.03
Heating capacity rated; kW	3.13	3.96	5.57	7.33
Air flow low / medium / high; m <sup>3</sup> /h	280 / 360 / 530	290 / 380 / 560	400 / 580 / 685	379 / 724 / 1092
Sound pressure low / medium / high; dB(A)	21.5 / 32 / 40	22 / 34 / 41	23 / 35 / 41	33 / 40 / 44.5
Sound pressure silence; dB(A) (x1)	20.5	21	22	21
Sound power level; dB(A)	55	55	59	65
Width / Height / Depth; mm	795 / 295 / 225	795 / 295 / 225	965 / 319 / 239	1140 / 275 / 370
Net weight; kg	10.2	10.2	12.3	20
Communication wiring; mm <sup>2</sup>	(3+T)x2,5	(3+T)x2,5	(3+T)x2,5	(3+T)x2,5
Liquid / Gas pipe diameter; inch	1/4" / 3/8"	1/4" / 3/8"	1/4" / 1/2"	3/8" / 5/8"

See compatibility of controllers in the range 1x1



## Onnix 2.0

KID-05.4 S  
Standard



Model	KAY-D 26 DR10	KAY-D 35 DR10	KAY-D 52 DR10
Cooling capacity rated; kW	2.63	3.52	5.28
Heating capacity rated; kW	2.93	3.81	5.57
Air flow low / medium / high; m <sup>3</sup> /h	425 / 515 / 700	425 / 515 / 700	430 / 530 / 750
Sound pressure low / medium / high; dB(A)	21.5 / 32.5 / 40	21.5 / 32.5 / 40	33.5 / 36.5 / 41
Sound power level; dB(A)	53	53	54
Width / Height / Depth; mm	921 / 321 / 211	921 / 321 / 211	921 / 321 / 211
Net weight; kg	11.3	11.3	11.3
Communication wiring; mm <sup>2</sup>	(3+T)x2,5	(3+T)x2,5	(3+T)x2,5
Liquid / Gas pipe diameter; inch	1/4" / 3/8"	1/4" / 3/8"	1/4" / 1/2"

See compatibility of controllers in the range 1x1

KID-06 S  
Standard



## Double Flow Console

Model	KSD-35 DR14	KSD-52 DR14
Cooling capacity rated; kW	3.52	5
Heating capacity rated; kW	3.81	5.28
Air flow low / medium / high; m <sup>3</sup> /h	490 / 580 / 650	600 / 690 / 780
Sound pressure low / medium / high; dB(A)	27 / 34 / 37	32 / 38 / 41
Sound power level; dB(A)	54	55
Width / Height / Depth; mm	794 / 621 / 206	794 / 621 / 206
Net weight; kg	14.9	14.9
Communication wiring; mm <sup>2</sup>	(3+T)x2,5	(3+T)x2,5
Liquid / Gas pipe diameter; inch	1/4" / 3/8"	1/4" / 1/2"

See compatibility of controllers in the range 1x1

KID-06 S  
Standard


## Cassettes 600x600 & 840x840

Model	KCI-26 DMR14	KCI-35 DR14	KCI-52 DR14	KCIS-71 DR14
Cooling capacity rated; kW	2.63	3.52	5.28	7.03
Heating capacity rated; kW	2.93	3.81	5.57	7.62
Air flow low / medium / high; m <sup>3</sup> /h	389 / 485 / 569	389 / 485 / 569	479 / 584 / 680	1000 / 1140 / 1300
Sound pressure low / medium / high; dB(A)	34.5 / 37.5 / 42	34.5 / 37.5 / 42	39 / 44 / 45.4	39.5 / 42.5 / 45.5
Sound power level; dB(A)	57	57	59	57
Width / Height / Depth; mm	570 / 260 / 570	570 / 260 / 570	570 / 260 / 570	830 / 205 / 830
Net weight; kg	16.3	16.3	16	21.6
Communication wiring; mm <sup>2</sup>	(3+T)x2,5	(3+T)x2,5	(3+T)x2,5	(3+T)x2,5
Liquid / Gas pipe diameter; inch	1/4" / 3/8"	1/4" / 3/8"	1/4" / 1/2"	3/8" / 5/8"
Panel; Width / Height / Depth; mm	647 / 50 / 647	647 / 50 / 647	647 / 50 / 647	950 / 55 / 950
Panel; Net weight; kg	2.5	2.5	2.5	6

See compatibility of controllers in the range Zen

## Ducts

 KCT-04.1 SPSWF  
Standard


Model	KPD-35 DR14	KPD-52 DR14	KPD-71 DR14
Cooling capacity rated; kW	3.52	5.28	7.03
Heating capacity rated; kW	3.81	5.57	7.62
Air flow low / medium / high; m <sup>3</sup> /h	300 / 480 / 600	515 / 706 / 911	825 / 1035 / 1229
Sound pressure low / medium / high; dB(A)	30 / 32 / 34.5	35 / 39 / 42	41 / 46 / 49
Sound power level; dB(A)	58	58	62
Max. pressure available; Pa	60	100	160
Air inlet width/height; mm	599/186	782/190	1001/228
Air outlet width/height; mm	537/152	706/136	926/175
Width / Height / Depth; mm	700 / 200 / 506	880 / 210 / 674	1100 / 249 / 774
Net weight; kg	17.8	24.4	32.30
Communication wiring; mm <sup>2</sup>	(3+T)x2,5	(3+T)x2,5	(3+T)x2,5
Liquid / Gas pipe diameter; inch	1/4" / 3/8"	1/4" / 1/2"	3/8" / 5/8"

See compatibility of controllers in the range Zen

## Hydraulic Kit



Compatible with outdoor unit KAM4-105 DR7

Model	KHHP-BI
Sound pressure; dB(A)	32
Sound power level; dB(A)	44
Width / Height / Depth; mm	490 / 918 / 325
Net weight; kg	56

For additional data check Aquatix chapter